



FOR AQMD USE ONLY:
AQMD S/R NUMBER: _____
BLDG/GRADING: _____

**El Dorado County
Air Quality Management District (AQMD)**

330 Fair Lane, Placerville, CA 95667
Phone: 530-621-7501 / Fax: 530-295-2774
www.edcgov.us/AirQualityManagement

Asbestos Dust Mitigation Plan (ADMP) Application

(For projects greater than 20 yd³ and located in Naturally Occurring Asbestos (NOA) designated areas as shown on the Western El Dorado County Asbestos Review Map, or where NOA had been discovered)

Please complete every section and initial each page – incomplete applications will be returned.

1. ADMINISTRATIVE INFORMATION	
Size of Project	Fees and Checklist
Estimated Size of DISTURBED area (acres) <input type="text"/> <i>(Round up to nearest acre)</i> <i>NOTE: If size of DISTURBED area exceeds 50 acres, the project is designated as a "Large Operation" and additional requirements apply.</i>	Fees due: \$386.00 ADMP Review Fee + _____ \$26 x DISTURBED Acres (minimum = \$26) \$ _____ Total Fees Due
Estimated VOLUME (cubic yards) of graded Material: <input type="text"/> <i>NOTE: If VOLUME of graded material exceeds 20 cubic yards, ADMP must be prepared and submitted.</i>	Checklist: <input type="checkbox"/> Fees submitted with ADMP Application <input type="checkbox"/> Application signed and initialed by a Responsible Party <input type="checkbox"/> Project Map (must be included) <input type="checkbox"/> NOA Sampling Reports (if applicable)
Will Export Soils be Generated? <input type="checkbox"/> YES <input type="checkbox"/> NO <i>If "YES": (1) Exported soil management MUST comply with Rule 223-2.6.D.3. (2) Address of the receiving site MUST be provided in Section 16.</i>	

2A. OWNER INFORMATION	2B. CONTRACTOR INFORMATION
Name:	<input type="checkbox"/> N/A
Mailing Address:	Name:
City/State: Zip:	Mailing Address:
Contact Name:	City/State: Zip:
Phone: Email/Fax:	Site Contact Name:
	Site Phone: Email/Fax:

3. PROJECT INFORMATION – Part I	
Address:	Project Description:
City/State/Zip:	Est. Project Start Date:
Parcel (APN) Number:	Est. Completion Date of Soil Disturbing Activities:

ADMP MUST BE AVAILABLE ON SITE AT ALL TIMES

ASBESTOS DUST MITIGATION PLAN APPLICATION

EL DORADO COUNTY AIR QUALITY MANAGEMENT DISTRICT

4. PROJECT NOA INFORMATION – Part II

Is Project Located In Asbestos Review Area? <input type="checkbox"/> YES <input type="checkbox"/> NO	Professional Geologist Report Attached? <input type="checkbox"/> YES <input type="checkbox"/> NO
If “NO”, Provide Date of NOA Discovery:	Laboratory Report/Data Sheets Attached? <input type="checkbox"/> YES <input type="checkbox"/> NO
Has Professional Geologist Evaluated the Site for NOA? <input type="checkbox"/> YES <input type="checkbox"/> NO (If “NO” Proceed to # 6)	Map Showing Location(s) of NOA ($\geq 0.25\%$) Attached? <input type="checkbox"/> YES <input type="checkbox"/> NO

5. PROFESSIONAL GEOLOGIST INFORMATION N/A

Name		
Address	City/State	Zip
Contact	Phone	Fax

6. MAP INFORMATION
(11x17 format or smaller preferred)

Map(s) clearly indicating the following **MUST** be included:

<input checked="" type="checkbox"/> Property lines / boundaries <input checked="" type="checkbox"/> Adjacent streets / easements <input checked="" type="checkbox"/> Areas to be disturbed or graded <input type="checkbox"/> Trenching areas <input type="checkbox"/> Excavation sites <input type="checkbox"/> Storage areas / piles	<input type="checkbox"/> Staging areas for removal <input type="checkbox"/> Truck routes <input type="checkbox"/> On-site parking lots <input type="checkbox"/> Landmarks and roads <input type="checkbox"/> NOA Sampling locations (<i>Indicate if $\geq 0.25\%$ NOA</i>) <input type="checkbox"/> Location(s) of placement of NOA containing excavated soils
---	--

7. PROJECT TYPE

Activity: (Check all that apply)

<input type="checkbox"/> Residential Construction <input type="checkbox"/> Grading <input type="checkbox"/> Road Construction <input type="checkbox"/> Road Maintenance <input type="checkbox"/> Housing Development	<input type="checkbox"/> Commercial Property Development <input type="checkbox"/> Pool Construction <input type="checkbox"/> Trenching / Utilities Work <input type="checkbox"/> Landscaping <input type="checkbox"/> Other (please describe): _____
--	---

Initial: _____
Responsible Person

ASBESTOS DUST MITIGATION PLAN APPLICATION
EL DORADO COUNTY AIR QUALITY MANAGEMENT DISTRICT

8. LARGE OPERATIONS (> 50 acres of DISTURBED surface) N/A

Additional requirements (Rule 223-2.7):

- Large Operations must include Dust Control Measures specified in Tables 5-6 of Rule 223-2.
 - Maintain daily records to document the specific dust control actions taken
 - Onsite Dust Control Supervisor (available within 30 minutes during working hours):

Name: _____ Phone/Mobile Number: _____

9. POTENTIAL SOURCES OF FUGITIVE DUST EMISSIONS

- There shall be no visible emissions (0% opacity as determined in accordance with US EPA Method 9) at 25 feet from the point-of-origin and at the property line. Visible emissions shall not exceed 20% opacity as determined in accordance with US EPA Method 9 at the point-of-origin. Applicable Best Management Practices included in Tables 1 - 4 of Rule 223-2 or similar effective measures shall be utilized to comply with standards per Rule 223-2.4.A.
- Asbestos Warning Signs must be posted at main entrances to the project (Rule 223-2.4.D)

Activity: (Check all that apply)

- | | |
|--|--|
| <input checked="" type="checkbox"/> Disturbing Soil | <input type="checkbox"/> Road Construction / Maintenance |
| <input type="checkbox"/> Clearing and Grubbing | <input type="checkbox"/> Stockpiles/Bulk Material Handling |
| <input type="checkbox"/> Grading | <input type="checkbox"/> Traffic Areas for Construction Activities |
| <input type="checkbox"/> Backfilling | <input type="checkbox"/> Trenching |
| <input type="checkbox"/> Clearing Forms, Foundations and Slabs | <input type="checkbox"/> Truck Loading |
| <input type="checkbox"/> Demolition – Mechanical/Manual | <input type="checkbox"/> Unpaved Road/Parking Lots |
| <input type="checkbox"/> Large Earth-moving Equipment Operations | <input type="checkbox"/> Blasting |
| <input type="checkbox"/> Importing/Exporting of Bulk Materials | <input type="checkbox"/> Other: _____ |
| <input type="checkbox"/> Landscaping | |

Initial: _____
Responsible Person

ASBESTOS DUST MITIGATION PLAN APPLICATION
EL DORADO COUNTY AIR QUALITY MANAGEMENT DISTRICT

10. SOIL DISTURBANCE ACTIVITIES

- There shall be no visible emissions (0% opacity as determined in accordance with US EPA Method 9) at 25 feet from the point-of-origin and at the property line. Visible emissions shall not exceed 20% opacity as determined in accordance with US EPA Method 9 at the point-of-origin. Applicable Best Management Practices included in Table 1 - 4 of Rule 223-2 or similar effective measures shall be utilized to comply with standards per Rule 223-2.4.A.
- Suspend soil disturbing activities when wind speeds are high enough to result in dust emissions in excess of standards in Rule 223-2.4.A, despite the application of dust mitigation measures

Controls for soil disturbing activities: (Check all that apply)

- Application of water, as necessary, prior and during earthmoving or land clearing activities (maintain live perennial vegetation where possible)
- Pre-wetting the ground to the depth of the anticipated cuts
- Stabilize soils once soils disturbing activities are complete
- Any other measure(s) as effective as the measures listed above (please describe)

11. ACTIVE STORAGE PILES N/A

- There shall be no visible emissions (0% opacity as determined in accordance with US EPA Method 9) at 25 feet from the point-of-origin and at the property line. Visible emissions shall not exceed 20% opacity as determined in accordance with US EPA Method 9 at the point-of-origin. Applicable Best Management Practices included in Table 1 - 4 of Rule 223-2 or similar effective measures shall be utilized to comply with standards per Rule 223-2.4.A.

The following control measure MUST be addressed:

- Keep active storage piles adequately wetted or covered with tarps (please describe):
- When handling bulk material apply water or chemical/organic stabilizers/suppressants
- Any other measure(s) as effective as the measures listed above (please describe)

Initial: _____
Responsible Person

ASBESTOS DUST MITIGATION PLAN APPLICATION
 EL DORADO COUNTY AIR QUALITY MANAGEMENT DISTRICT

12. INACTIVE STORAGE PILES N/A
 (not disturbed for more than 7 consecutive days)

- There shall be no visible emissions (0% opacity as determined in accordance with US EPA Method 9) at 25 feet from the point-of-origin and at the property line. Visible emissions shall not exceed 20% opacity as determined in accordance with US EPA Method 9 at the point-of-origin. Applicable Best Management Practices included in Table 1 - 4 of Rule 223-2 or similar effective measures shall be utilized to comply with standards per Rule 223-2.4.A.

Control for disturbed surface areas and storage piles that will remain inactive for more than seven (7) days shall include one or more of the following: (Check all that apply)

- Keep the surface adequately wetted
- Establish and maintenance of surface crusting sufficient to satisfy the test in Rule 223-2.10.C or Title 14 subsection §93105(h)(6)
- Application of chemical dust suppressants or chemical stabilizers according to the manufacturer's recommendations
- Covering with tarp(s) or vegetative cover
- Installation of wind barriers of fifty (50) percent porosity around three (3) sides of a storage pile
- Installation of wind barriers across open areas
- Any other measure(s) as effective as the measures listed above (please describe)

13. TRACK-OUT PREVENTION

- Any visible track-out on a paved public road where vehicles enter and exit the work area must be **IMMEDIATELY** removed from paved public roads. Removal shall be accomplished by using wet sweeping or a HEPA filter equipped vacuum device or flushing with water (if not in violation of any National Pollutant Discharge Elimination System permit program). Applicable Best Management Practices included in Table 3 of Rule 223-2 or similar effective measures shall be utilized to comply with standards per Rule 223-2.4.A. *Note: The use of blower devices, or dry rotary brushes, is expressly prohibited!*

Other control measures: (Check all that apply)

- A gravel pad designed using good engineering practices to clean the tires of exiting vehicles
- Grizzlies, or similar devices designed to remove mud/dirt from tires
- A tire shaker
- A wheel wash system (mechanical or manual)
- Paving of interior roads
- Any other measure(s) as effective as the measures listed above (please describe)

Initial: _____
 Responsible Person

ASBESTOS DUST MITIGATION PLAN APPLICATION
 EL DORADO COUNTY AIR QUALITY MANAGEMENT DISTRICT

14. BLASTING ACTIVITIES N/A
Must notify AQMD two (2) hours prior to blast!

- There shall be no visible emissions (0% opacity as determined in accordance with US EPA Method 9) at 25 feet from the point-of-origin and at the property line. Visible emissions shall not exceed 20% opacity as determined in accordance with US EPA Method 9 at the point-of-origin. Applicable Best Management Practices included in Table 1 - 4 of Rule 223-2 or similar effective measures shall be utilized to comply with standards per Rule 223-2.4.A.
- Suspend blasting activities when wind speeds are high enough to result in dust emissions in excess of standards in Rule 223-2.4.A, despite the application of dust mitigation measures. Consider wind direction with respect to property line and nearby residences

Controls for blasting activities: (Check all that apply)

- Pre-wetting blast area
 - Place blast mats or soil mounds over charges
 - Stabilize soils once blasting activities are complete
 - Any other measure(s) as effective as the measures listed above (please describe)
- _____
- _____
- _____

15. TRAFFIC CONTROL OF ON-SITE UNPAVED ROADS, PARKING LOTS AND STAGING AREAS N/A

The following control measure MUST be addressed:

- A maximum speed limit of fifteen (15) miles per hour (mph) or less

Additional control measures: (Check all that apply)

- Water every two hours of active operation or sufficiently often to keep the area adequately wetted
 - Apply chemical dust suppressants consistent with manufacturer's directions
 - Maintain a gravel cover with a silt content that is less than five (5) percent and asbestos content that is less than 0.25 percent, as determined using an approved asbestos bulk test method, to a depth of three (3) inches on the surface being used for travel
 - Direct construction traffic over established haul routes
 - Any other measure(s) as effective as the measures listed above (please describe)
- _____
- _____
- _____

Initial: _____
 Responsible Person

ASBESTOS DUST MITIGATION PLAN APPLICATION
 EL DORADO COUNTY AIR QUALITY MANAGEMENT DISTRICT

16. MANAGEMENT OF EXCAVATED SOILS

The owner and/or operator **MUST** ensure that procedures and documentation per Rule 223-2.6.D. are obtained and retained.

- On-Site Disposition.** Where feasible, excavated soils should be placed into fills elsewhere on the project.
 - **Location(s)** of removal and placement quantities and location(s) of fills must be documented **and records retained for a period of ten (10) years.**
 - Fills, with a NOA content $\geq 1.0\%$ or when visually evident fibrous materials likely to be NOA are present, located in residential landscaping areas shall be covered by at least two feet (24 inches) of non-asbestiform cover soil material, or by concrete or asphalt paving.
- Off-Site Disposition.** For any **soils** transported off-site the following information must be documented and retained for a period of at least 3 years (Rule 223-2.6.D.3).
 - Originating project information (name, address, location)
 - Laboratory results/report for NOA soil testing done at the project location
 - Date(s) of off-site transport(s) of excavated soils
 - Location(s) of transported soil
 - Total quantity transported to each location
 - Intended usage (fill, surface application), if the final destination is other than Class II or Class III landfill disposal
 - **Location to receive exported soils:** _____

NOTE: It is the owner/operator responsibility that final disposition (usage or disposal) and transport of excavated materials from the project are in compliance with pertinent federal, state and local rules and regulations, including CA Title 17, Section 93106, Asbestos Airborne Toxic Control Measure for Surfacing Applications.

17. OFF-SITE TRANSPORT N/A

The owner and/or operator must ensure that no trucks are allowed to transport excavated material off-site unless:

- Trucks are maintained such that no spillage can occur from holes or other openings in cargo compartments
- Loads are adequately wetted

Water applied, if necessary, to the top of load

AND either: (Check all that apply)

- Covered with tarps or other suitable cover
- Trucks loaded such that the freeboard is not less than six (6) inches (material does not touch the front, back or sides of the cargo compartment at any point less than six inches from the top)
- Any other measure(s) as effective as the measures listed above (please describe)

NOTE: It is the owner/operator responsibility that final disposition (usage or disposal) and transport of excavated materials from the project are in compliance with pertinent federal, state and local rules and regulations, including CA Title 17, Section 93106, Asbestos Airborne Toxic Control Measure for Surfacing Applications.

Initial: _____
 Responsible Person

ASBESTOS DUST MITIGATION PLAN APPLICATION

COUNTY OF EL DORADO AIR QUALITY MANAGEMENT DISTRICT

18. POST CONSTRUCTION STABILIZATION OF DISTURBED AREAS

■ Upon completion of all phases of the project, but **no later than 30 days following the end of soil disturbing activities**, all disturbed surfaces with naturally occurring asbestos content of equal to or greater than 0.25% shall be stabilized using one or more of the following methods:

- Establish a vegetative cover (less than 30% of disturbed ground exposed within 90 days of planting, and at all times thereafter):
- Placement of at least three (3.0) inches of non-asbestos containing material on disturbed soil areas in residential and nonresidential areas;
- Placement of a total of at least twelve (12) inches or the maximum depth of irrigation improvements, whichever is higher, of non-asbestos containing material on disturbed soil areas in residential landscaping areas with NOA content greater than 0.25% or when visually evident fibrous materials likely to be asbestos are present;
- Paving, decking, building foundations, swimming pool structure, flatwork or retaining walls;
- Other measures approved by the APCO:

19. STATEMENT OF PROJECT'S RESPONSIBLE PARTY

(Owner or Licensed Contractor acting on behalf of the Owner)

"I am familiar with the Rules and Regulations of the County of El Dorado AQMD that are applicable to my project and I certify that the information and the data submitted with the application are true with regards to the project activities and/or equipment which are the subjects of this application". **A copy of this plan must be provided to all contractors and be available on site at all times.**

NOTE: Any changes to this plan MUST be pre-approved by the AQMD.

Name (print)	Name (sign)
Title	Date
Address	Phone Number

FOR AQMD USE ONLY

DATE STAMP	<input type="checkbox"/> <u>APPLICATION APPROVED</u>	<input type="checkbox"/> <u>APPLICATION NOT APPROVED</u>
	DATE: _____	
	REVIEWER NAME: _____	
	REVIEWER SIGNATURE: _____	
COMMENTS:		

WARNING

Soils in the area may contain Naturally Occurring Asbestos (NOA). Asbestos is a known carcinogen.

Report excessive fugitive dust to the contractor at:

or EDCAQMD: 530-621-7501

This page intentionally left blank.

Receipt for Offsite Reuse of Restricted Soils/Materials with <0.25% Naturally Occurring Asbestos (NOA) for Surfacing and Non-surfacing Applications

A copy of this receipt and any associated soils sampling reports and results must be retained by the supplier of the restricted soil/materials and provided to all recipients. Restricted soil/materials are those that originated from a designated Asbestos Review Area. See El Dorado County Air Quality Management District Rule 223-2. and California Air Toxic Control Measure 93106. All fields must be completed.

Originating Project Location:

Address/Name: _____

APN Number: _____

Grading/Building Permit Number(s): _____

Certification by Originating Location Responsible Party:

"I certify that the restricted soils/materials have been evaluated, tested and analyzed for naturally occurring asbestos (NOA). The reported asbestos concentration is less than 0.25%. I am familiar with the Rules and Regulations of the El Dorado County AQMD that are applicable to above referenced excavated materials and I certify that the information and the data provided are true to the best of my knowledge".

Name (print): _____ Title: _____

Signature: _____ Date: _____

Delivery Location:

Address/Name: _____

APN Number: _____

Total Est. Quantity Delivered (cubic yards or tons): _____

Date of Delivery: _____

Planned use of Soils/Materials:

On Site: _____

Off Site: _____

Acknowledgement by Receiving Location Responsible Party:

"I acknowledge receiving the soils/materials as described above"

Name (print): _____ Title: _____

Signature: _____ Date: _____

Receipt for Offsite Reuse of Restricted Soils/Materials with $\geq 0.25\%$ Naturally Occurring Asbestos (NOA) for Non-surfacing Applications

A copy of this receipt and any associated soils sampling reports and results must be retained by the supplier of the restricted soil/materials and provided to all recipients. Restricted soil/materials are those that originated from a designated Asbestos Review Area. See El Dorado County Air Quality Management District Rule 223-2. and California Air Toxic Control Measure 93106. All fields must be completed.

Originating Project Location Info:

Address/Name: _____

APN Number: _____

Grading/Building Permit Number(s): _____

Certification by Originating Location Responsible Official

"I certify that the restricted soils/materials have been evaluated, tested and analyzed for naturally occurring asbestos (NOA). The reported asbestos concentration is _____. I am familiar with the Rules and Regulations of the El Dorado County AQMD that are applicable to above referenced excavated materials and I certify that the information and the data provided are true to the best of my knowledge".

Responsible Official Name (print)/Title: _____

Responsible Official Name (sign)/Date: _____

DELIVERY Location Information:

Date: _____

Address/Name: _____

APN Number: _____

Total Est. Quantity Delivered (cubic yards or tons): _____

Planned use of Delivered Soils/Materials:

On Site: _____

Off Site: _____

Provide address/ name/ APN Number of new location.

DELIVERY Location Responsible Official

WARNING: It is unlawful to use this material for surfacing or any application in which it would remain exposed and subject to possible disturbances. Materials must be handled in compliance with applicable requirements of EDCAQMD Rule 223-2 (Fugitive Dust – Asbestos Hazard Mitigation).

Note: Acceptance of this soil/material may require future construction projects on your property to comply with requirements of EDCAQMD Rule 223-2.

Delivery Accepted by Name (print)/Title: _____

Delivery Accepted by Name (sign)/Date: _____